

Technical Data Sheet



Oil Booster



Reaction time
works during operation



Application field
for use in all diesel and
gasoline engines



Consumption
60 ml for 1 L



Application interval
with every oil change or
on demand

Application

Compatible with all mineral and synthetic engine oils. Sufficient to treat 5 L of engine oil. Add after the oil change or if needed to the warm, new engine oil. For larger volumes add 60 ml Oil Booster per liter engine oil. Works during operation.

Attention: Check engine oil level before application!

Description

GAT Oil Booster contains a highly effective additive package for increased wear and tear protection properties of all types of engine oils. Reduces wear and tear, protects against corrosion, prevents from deposits in the oil and lubrication system and combats harmful engine acids.

Advantages

Increased reliability of operation and prolonged life span of all components. Has positive effects on oil consumption, motor performance, emission values and the life time of the catalytic converter.

Packing sizes	Packing Unit	Article Number
300 ml	24 x 300 ml	Art. 62116
1 L	12 x 1 L	Art. 62081
5 L	-	Art. 62082
10 L	-	Art. 62083

other sizes available on request

Properties

Physical state	viscous
Color	dark amber
Density	0,9 g/cm ³
Flash point	>200 °C

Compatibility

Compatible with all mineral and synthetic engine oils.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.