

Technical Data Sheet



Reaction time
works during operation



Consumption
50 ml for 1 liter



Application field
for use in all diesel and gasoline engines



Application interval
on demand

Engine Oil Stop Leak

Application

Compatible with all mineral and synthetic engine oils. Sufficient for up to 5 L of engine oil. Add to the engine oil. For larger volumes add 50 ml of the product per liter engine oil. Works during operation.

Attention: Check engine oil level before application! We recommend cleaning of the oil system with Engine Cleaners before application.

Description

GAT Engine Oil Stop Leak contains a highly effective additive package to stop loss of engine oil caused by leakage. Helps to regenerate engine gaskets and keeps them soft and supple. Prevents oil loss through bearing seals and valve covers.

Advantages

Only a well-functioning engine can run on full power! Easy to use – no extra effort. Reduction of oil loss, improved reliability of operation, increased engine performance, less wear and tear.

Packing sizes	Packing Unit	Article Number
300 ml	24 x 300 ml	Art. 62077
200 L	–	Art. 62277

other sizes available on request

Properties

Physical state	liquid
Color	dark amber
Density	0,86 g/cm ³ DIN 12185
Flash point	72 °C ISO 3679
Viscosity	9 mm ² /s (@40°C) DIN EN ISO 3104

Compatibility

Compatible with all mineral and synthetic engine oils.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.